Portable Ladder Safety Checklist

Campus: Bu	ilding	Room			Sup	upervisor		
Date:						_		
Audit Performed by:			Y E S	N O	N A	N Brief Comment		
A. Inspection Guidelines for Portable Ladders (including Extension Ladders and Step Ladders)								
1. Wooden ladders free of splinters, sharp slivers, dents that would weaken.	edges, cracks or decay. N	letal ladders free of						
2. No rungs/steps missing or damaged so	as to make them unsafe					-		
3. Surfaces free of mud, oil, grease, or sli corrugated, knurled, dimpled or coated		lder, rungs must be						
4. Joints between steps and side rails tigh	t and rungs do not move wl	hen twisted by hand						
5. Hardware and fittings securely attached	l					_		
6. Moveable parts operate freely without b	inding or undue play							
7. Safety feet and other auxiliary equipme	nt in good condition							
8. No opaque coating which might obscur	e defects; labels on only on	e face of side rails						
9. Rope, if present, in good condition (not	frayed/badly worn)					_		
10. Spreader on step ladder in good condition	on					_		
11. If determined to be defective, attach wa	rning label and withdraw la	dder from service				_		
B. Ladder Use Safety Tips - Selection and Placement								
1. No overhead electrical lines or other ele	ectrocution hazards in vicini	ty of use				_		
2. Metal ladder NOT USED for electrical	work or near energized elec	ctrical circuits						
 Ladder length does not exceed allowab 30';2-section wood ladder, 60'; 2-sectio than 2 sections, 60') 						_		

		Y E	N O	N A	Brief Comment
		S			
4.	Ladder length appropriate for task (not too long or too short)				
5.	Ladder set at proper angle and with both rails supported equally				
6.	Ladder not used as a guy, skid, scaffold, or any use other than its intended purpose.				
7.	Ladder placed to prevent slipping, or lashed or held in position (Step ladders have all 4 feet on firm footing.)				
8.	Ladder placed only on stable base (no boxes, etc. used to gain height). Ladder does not lean to one side or wobble.				
9.	In traffic areas, measures taken to prevent accidental displacement (Doors locked or guarded prior to placing ladder in front of them, barricade around work area, etc.)				
10.	When used to access a high landing or rooftop, top of ladder extends 3' above edge of landing.				
C. Ladder Use Safety Tips - Climbing and Working From					
1.	Only one person on ladder at a time.				
2.	Face ladder when climbing.				
3.	Do not get on or off ladder from side or back. (If step ladder, do not use rear braces as steps unless so designed by manufacturer)				
4.	Maintain 3-point contact with ladder at all times when climbing.				
5.	If working from ladder, keep body aligned with center of steps/rungs and do not lean backwards.				
D. Training					
1.	User trained in proper use of, and hazards related to, ladders				

Key: If you have answered "NO" to any question in part A, do not use the inspected ladder. Mark it with a warning label and report its defectiveness to the area supervisor. If you have not received training in ladder safety (Part D), do not use a ladder on the job. Use Parts B and C as reminders of safe work practices when using a ladder.